



## ANSI-ASC-C63<sup>®</sup> Interpretation Request Form

This form shall be used for submission of Interpretation Requests related to ANSI-IEEE standards that are within the responsibility of ANSI-ASC-C63<sup>®</sup>. The eight parts of the form must be filled out completely, with the exception of the Subcommittee Response, to ensure expedient processing. This completed form is to be submitted to the [Secretary of ANSI-ASC-C63<sup>®</sup>](#) via e-mail.

Submission Date	Originator Name, Company
02/20/2015	Takashi Maruyama / LAB. Support Ltd.

Standard	Clause/ Sub clause	Paragraph Figure/ Table	Type (General/ Technical/ Editorial)	Comment / Inquiry	Subcommittee Response (to be filled in by Subcommittee Chair)
C63.4-2014	8.3.1.2 Exploratory radiated emissions measurements (1 GHz to 40 GHz)		Technical	<p>When measuring emissions above 1 GHz, the frequencies of maximum emission shall be determined by manually <b>(or with an articulated antenna positioner)</b> positioning the antenna close to the EUT and then moving the measurement antenna over the surfaces of the EUT while observing a spectral display.</p> <p>Is positioning the antenna <b>close to the EUT</b> required, when we use with an articulated antenna positioner?</p>	<p>The answer is simply, yes. When a measurement is performed manually and/or using an articulated (automated or manual) antenna mast, the positioning of the antenna close to the EUT is required regardless if the antenna is hand held or mounted on a mast.</p>